PLC-WXL46

WXGA ULTRA SHORTFORCUS PROJECTOR

3LCD | Built-in Network | Ultra Short-Throw | Closed Caption

SHORT THROW PROJECTION FROM ONLY 34 INCHES AWAY
The PLC-WXL46 can project a full 80-inch image from a distance of only 34 inches. Teachers can project images onto the blackboard right from their desk. This means they can use large images even in relatively small rooms.

WXGA , FITS A VARIETY OF APPLICATION SITUATIONS
Offering a wide XGA full 1280 x 800 (16:10) resolution, the PLC-WXL46 makes it possible to project HD images. This projector is equally comfortable with exquisite HD images from cable/satellite or DVD sources as it is delivering a PC-based presentation in the class room.

NETWORKING CAPABILITY
The PLC-WXL46 is equipped with SANYO's exclusive PJ Network Interface for wired networking. A common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser. Emails can be sent automatically to report operating status.

BLACKBOARD, COLOR BOARD MODE
In classrooms and other places where there is no screen available, images can be projected onto the blackboard and color board. This enables quick response when making lesson changes or calling a quick meeting.

SPACE SAVING DESIGN
The use of a short-throw lens makes it possible to move the projector from the center of the classroom or meeting room, to a spot closer to the screen. This frees up more room space, and cuts down on the possibility of viewers blocking the image with their shadows.

EASY ON/OFF FUNCTION
The power turns on as soon as you connect the power cord. No need to press any buttons on the remote control or projector. You can disconnect the power cord as soon as the power is turned off.

COMPLETE SECURITY FUNCTIONS
The PIN code lock guards from an unauthorized user. Anti theft alarm function sounds loudly to prevent theft, when a vibration is detected.

CLOSED CAPTION
PLC-WXL46 is Closed Caption compatible.

Resolution		WXGA(1280 x 800)
Brightness (typical)		2000 Lm
Contrast Ratio (Full on / off)		500:1
Image Size		50"-110"
Aspect Ratio		16:10
Projection Lamp		200W
Scanning Frequency		H:15-100kHz, V:50-100Hz
Fan Noise		31.0 dBA (Eco)
Voltage		100-240V AC (auto voltage) ; 50/60 Hz
Power Consumption		200W (Eco)
Input signal compatibility		UXGA/WXGA/SXGA+/SXGA/XGA/SVGA/VGA/MAC/ 1080i/50/1080i/60/1035i/720p/480p/480i/575p/575i
Color System		NTSC/PAL/SECAM/NTSC4.43/PAL-M/PAL-N
Projection Lens (inch)		F 1.80 f=0.26"
Throw Ratio		0.50 : 1
Throw Distance (feet)		1.7' - 3.9'
Zoom / Focus		Fixed/Manual
Up / Down Ratio		N/A
Digital Keystone Correction		V +/- 20° (Auto Keystone)
Digital Zoom		16x - 1/4x
Speaker Output		1W
Weight (lbs)		7.5 lbs.
Dimensions (inch) W,H,D		12.6"x5.7"x11.8"
Replacement Lamp		610 332 3855
Replacement Remote		645 086 4964
Lamp Life * (hours)		3000h (Eco)
Input	PC/Video	D-sub 15 x 2 (RGB, S-Video) Mini DIN 4pin x 1 (S-Video) RCA x 1 (Component) RCA x 1 (Composite)
	Audio	Stereo mini jack x 1 RCA x 2
Output	PC/Video	D-sub 15 x 1 (Monitor out)
	Audio	Stereo mini jack x 1
Other Feature		Mini DIN 8pin x 1 (RS232C) RJ-45 x 1
Included Accessories		AC power cord x 1 VGA cord x 1 Quick reference guide Owner's manual x 1 (CD-ROM) Quick manual x 1 CD-ROM read me note x 1 CD ROM (Application software for Network) x 1 Remote control x 1 (AA battery x 2) PIN code Label
Warranty		Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.

Back Panel

PRESENTATION TECHNOLOGIES
21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax: 818-717-2719
www.sanyoprojectors.com

©2009 SANYO